

DATE _____ PROJECT _____ TYPE _____ QUANTITY _____

iLas® Aimable Indexing LED Luminaire

FEATURES

- Constant current luminaire
- Dedicated driver per fixture within framing system
- Designed to work with iLas Framing (sold separately, required)
- Continuous runs mounted end to end for seamless installation
- LEDs adjust at 30° to graze or wall wash
- CRI 85+



FIXTURE COMPONENTS INCLUDE:
iLas fixture

FIXTURE COMPONENTS REQUIRED (SOLD SEPERATELY):
Framing system

CONSTRUCTION

- Extruded aluminum luminaire body with adjustment control.
- Proprietary injection molded optics with true asymmetric distribution
- Satin anodized finish

ELECTRICAL

- Integral driver 120-277V.
- Dimmable hi-flux LEDs with minimal pitch.

ORDERING

PRODUCT	POWER	LENGTH	LED COLOR	OPTICS	CONTROL	ACCESSORIES
iLas Asymmetric LED Luminaire for iLas Pocket System	07 7.6 watts / linear ft	22 22 ⁷ / ₈ " actual	W2 2700K	A Asymmetric	ND Non-Dim	WL White 45° Louver EM Emergency battery pack (consult factory) EM-C Emergency circuit wiring (consult factory)
	10 10.5 watts / linear ft ¹	34 34 ¹ / ₂ " actual	W3 3000K		D 1%, 0-10V Dim	
		45 45 ¹ / ₄ " actual	W35 3500K		S Lutron ECO 1% Soft On Fade To Black PEQ1 ³	
		67 67 ³ / ₄ " actual	W4 4000K		Lo Lutron Hi-Lume 1% EcoSystem with Soft On, Fade to Black LDE1 ³	
		90 90 ¹ / ₈ " actual ²			T Lutron Hi-Lume 1% 120V 2-Wire LTEA ³	
			LD 5-series EcoSystem LED driver LDE5 ³			
	¹ High Power driven at 9.8 watts / linear foot for Lutron drivers	² 90 only available in 7.6 watt			³ 4ft max length for Lutron options	

RATINGS & CERTIFICATION

- cETLus Listed
- Made in the USA
- Average rated LED life of 50,000 hours @ 70% lumen output




LUMEN OUTPUT

STANDARD	429 Lm/ft	7.6 W/ft	57 Lm/w
HIGH	593 Lm/ft	10.5 W/ft	57 Lm/w

WARRANTY 5 Year warranty

visit electrixillumination.com for details

PHOTOMETRY



High Power Aymmetric

IES data available on electrix website electrixillumination.com

DIMENSIONS

